

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 100343

PRIMARY CORNER DESCRIPTION E 1/4 Cor. for Sec. 24 only, T20-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 1 Page(s) 10)

-----  
Set qr. sec. post; from which  
A Spruce 24" dia., bears S.47°W., 6 lks. dist.  
A Spruce 18" dia., bears S.41°E., 22 lks. dist.

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 745 survey dated May 1, 1902 (DCS0 records Vol. 1 Page(s) 77-78)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S 24 on W. face; from which  
A Spruce 30" dia., bears S.28°E., 13 lks. dist. mkd. ¼ S BT.  
A Spruce 36" dia., bears S.69°W., 19 lks. dist. mkd. ¼ S24 BT.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249-1 and M 22-36

-----  
This point is marked by a 1" pipe with lead filled bell marked for E ¼ corner Sec. 24 and witnessed by a:  
64" Spruce stump S.66°13'W., 16.40 ft. The scribing is visible.

Fd. OK, Feb. 1993 by John Minor - M 116-56  
Fd. OK, June 1996 by John Minor - M 125-26