

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 156-57)

Intersect West bdy. of Tp., 355 lks. S. of cor. to secs. 18, 19, 13 and 24. At point of intersection I set a post 4½ ft. long, 4" sq., 24" in the ground for closing cor. to secs. 18 and 19, marked S18 on N.; CC T20S R11W on E.; S19 on S. face, with 3 notches on S. and N. faces; from which
A Chittem 5" dia., bears N.25°E., 30 lks. dist. mkd. T20S R11W S18 BT.
An Alder 12" dia., bears S.35°E., 18 lks. dist. mkd. T20S R11W S19 BT.
A Chittem 8" dia., bears N.88°W., 18 lks. dist. mkd. T20S R11W CC S18 & 19 BT.

June 15, 1892

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249 and M 22-36

C C is a 1½" pipe in a swamp, approx. 15 ft. from the toe of the slope. No bearing trees.

John Minor - For: Menasha Corp. - Feb. 1993 - M 116-56

Found - 1½" iron pipe 5.5 ft. above ground.
30" Doug. Fir, N.20°E., 52.8' (Orig. unknown)
24" Doug. Fir, N.36°W., 55.0' (Orig. unknown)
1½" iron pipe, N. 9°W., 36.4' (Orig. unknown)

Fd. OK, June 1996 by John Minor - M 125-26