

PRIMARY CORNER DESCRIPTION Sec. cor. for 13 & 24 only, T20-12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 113-114)

Set a post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 13, 18, 19 and 24, marked T20S S18 on NE.; R11W S19 on SE.; R12W S24 on SW.; S13 on NW. faces, with 3 notches on N. & S. edges; from which

- A Hemlock 10" dia., bears N.65½°E., 11 lks. dist. mkd. T20S R11W S18 BT.
- A Fir 12" dia., bears S.26°E., 20 lks. dist. mkd. T20S R11W S19 BT.
- A Hemlock 14" dia., bears S.46°W., 11 lks. dist. mkd. T20S R12W S24 BT.
- A Hemlock 4" dia., bears N.25°W., 9 lks. dist. mkd. T20S R12W S13 BT.

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902, - (DCSO records Vol. 1 Page(s) 66)

At cor. of secs. 13 and 24, T20S R12W, where I find witness trees cut down, stumps and cor. standing and agreeing with notes furnished by the Surveyor General.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249 and M 22-36

Corner marked by a 1¼" Iron pipe at the top of a bank East of Slonecker's house, and witnessed as follows:

- 11" Spruce S.17°10'W., 48.10 ft.
- 14" Holly S.22°30'W., 44.60 ft.
- 12" Apple N.27°15'W., 35.50 ft.

John Minor - For: Menasha Corp. - Feb. 1993 - M 116-56

Found - Two 3/4" iron pipes side by side. Orig. unknown. A 1½" iron pipe is called for in M22-36.

- 15" Holly S.23°W., 44.6', side center.
- 14" Apple N.23°W., 34.7', side center.
- 48" Spruce S.15°E., 48.5', side center (rec. S.17°10'W., 48.10')