

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 100569

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 7

Alias <u>949160</u>	Description <u>M.C. So. shore Lake Tsiltcoos</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 11)

Set meander post; from which
A Spruce 10" dia., bears S.61°W., 42 lks. dist.
An Alder 8" dia., bears S.76°E., 88 lks. dist.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 70)

Intersect South shore of Lake Tsiltcoos. Unable to find any trace of meander cor. or witnesses thereto, re-establish a corner at this point by setting a willow post, 4 ft. long, 4" sq., 24" in the ground, marked M C on the S.; T20S on the N.; R11W S7 on the E.; and R12W S12 on the W. faces, for the meander cor. of fracl. secs. 7 and 12 S. of lake and from which:
A Fir 12" dia., bears S.70°E., 14 lks. dist. mkd. T20S R11W S7 MC BT.
A Fir 10" dia., bears S.30°W., 22 lks. dist. mkd. T20S R12W S12 MC BT.

Survey by Daniel Baker - For: International Paper Co. and Davidson Industries - July 1988 - M 106-67

(Point 1366.62 ft. southerly of point for sec. cor. for 1 and 12)
Set 3/4" x 42" alum. rod and cap mkd. "RLS 1978 MC S12 S7 T20S R12W R11 1988", from which
30" Spruce N.44°E., 68.5 ft. scribed MC S7 BT.
16" Alder S.28°W., 11.8 ft. bark scribed MC S12 BT.