

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; and 6, T21-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 117)

Set a post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which

- A Fir 36" dia., bears N.8°W., 16 lks. dist. mkd. ¼ S BT
- A Fir 48" dia., bears S.29°W., 45 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - Larry E. Monrean - Peter Earle - Mike Tompkins - 12/16/1976 - C.S. file 59/26-24 (added 4/11/2016)

Not Found

We found a point where two squared posts have been set. One old, decayed approx. 20" high, the second stake is new approx. 40" high, from this point:

A fir snag 33" dia., bears N.11°W., 12.8 ft. This tree has several old blazes. I open scared portion of tree facing stakes. No scribing fd.

A fir stump 40" dia., bears S.39°W., 29.4. Found old axe marks. We opened portion facing stakes, no scribing fd. There are blazed lines running West & north, area looks OK for calls.

Douglas County Surveyors Office - Gary L. Langlitz, Deputy - R.B. Kimberling; P.L. Earle; S.J. Flause - For: Doug. Co. Land Dept. - Sept. 1977 - C.S. File 59/32; C.S. File 59/40-7 and RM 3-13

No monuments or accessories found.

Position determined by single proportionate measurement. Set at corner point, a 1" x 30" I.P. 26" in the ground on a steep SE slope, with brass cap attached marked:

County Surveyors Office

T 20 S
R 11 W S 31 1/4
 S 6

T 21 S

BTs - An 18" D.Fir double blazed and scribed "¼ S6 CS BT" bears S.18°W., 29.8 ft.

A 14" D.Fir double blazed and scribed "¼ S31 CS BT" bears N.31°W., 18.3 ft.

Corner is located approx. 100 ft. East of top of spur ridge running NE.

continued next page

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; and 6, T21-11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

John C. Bentley, for I.P. Timberlands Operating Co., Ltd.
Feb. 1995 -M121-68.

Found - 2½" dia. County Surveyor's Office brass cap on a 1½"
iron pipe, 8" above ground. (C.S. 59/40)
24" D.Fir, S.19°W., 29.4 ft. Healed face. (rec.
S.18°W., 29.8 ft.)
19" D.Fir, N.31°W., 18.6 ft. Healed face. (rec. 18.3
ft.)
New BTs- 25" D.Fir, N.52°E., 26.2 ft. scribed "¼ S31 BT"
19" D.Fir, S.78°E., 67.9 ft. scribed "¼ S6 BT"