

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 140440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. -  
Jan. 30, 1963 - C.S. File 51/249-1 (PG 12/17) and M 22-36

-----  
Marked by a 1" Iron pipe with bell filled with lead and  
witnessed by a:

64" Spruce stump S.12½°W., 43.35 ft.

60" Spruce stump N.29½°W., 14.7 ft.

(as shown in field notes of previous survey)

I mark: 6" Spruce S.66°W., 21.8 ft.

This corner is about 100 ft. East of the County Road.

Fd. OK, June 1996 by John Minor - M 125-26

Tony Hostetter - For: D.R. Johnson Lumber Co. - 8/3/2017 -  
C.S. File 65/95-55

-----  
Found - 1" iron pipe, lead filled bell, described by Hootman  
in 1963 ( M22-36 )

Hootman BTs now stumps.

New BTs- 12" Alder, scribed "S18 C¼ BT", BT tag, bears;  
N.06°E., 31.3 ft to spike.

15" Spruce, scribed "S18 C¼ BT", BT tag, bears;  
S.30°E., 38.9 feet to spike.