

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 162)

(40.00 chs.)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which

An Alder 10" dia., bears N.1½°E., 9 lks. dist. mkd. ¼ S BT

A Hemlock 10" dia., bears S.9½°E., 23 lks. dist. mkd. ¼ S BT.

(41.85 chs. West)

Fir 36" dia., which I marked with 2 notches on E. and W. sides. This Fir stands near foot of hill, from whence a marsh, covered by water and impassable, reaches to Ten Mile Lake.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron - March 30, 1970 - C.S. File 53/66-96

Found - No trace of original BTs, however, find old 36" now 60" Fir Line Tree mkd. with 2 notches on East and West sides at foot of hill as described. This line tree bears West 122.1 ft.

From this point, Set for temp ¼ corner, we chain East to top of spur, record call distance was 528.0 ft., we measure 529.2 ft. Because the calls check so well from old line tree and spur, WE SET: Brass cap at cor. mkd: County Surveyors Office

T 20 S R 11 W

¼ $\frac{S}{S}$ $\frac{6}{7}$
1970

Set 6.0 ft. steel fence post on W. side of brass cap.

New BTs- 10" D.Fir S.26°W., 78.2 ft. mkd. ¼ S7 CS BT.

60" D.Fir West, 122.1 ft. mkd. ¼ S6 CS BT.

Corner lies on West edge of old logging road.

Fd. OK, July 1988 by D. Baker - M 106-67