

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 147)

Set a post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
 A spruce, 3" dia., bears S.11°W., 36 lks., mkd: ¼ S BT.
 A hemlock, 4" dia., bears N.72°E., 44 lks., mkd: ¼ S BT.

Tony Hostetter - For: Rosboro LLC Co. - April 2008 - M155-72

Found - 3 BTs on record in Roseburg Resources Reedsport Office. (formerly International Paper company.)
Set - 5/8" rebar w/plastic cap mkd "HOSTETTER LS 1975", using distances listed on IP tags, from which
 8" Fir, IP tag, bears S.38°E., 12.1 ft.
 8" fir, IP tag, bears N.19°E., 15.9 ft.
 24" fir stump, IP tag, S.80°E., 9.7 ft.
New BT - 13" fir, scribed "S32 ¼ BT", bears, S.84°E., 2.3 ft to spike.