

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 151)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 19, 20, 29 and 30, mkd. T20S S20 on NE.; R11W S29 on SE.; S30 on SW.; S19 on NW. faces, with 2 notches on S. and 5 notches on E. edges; from which

An Alder 6" dia., bears N.36°E., 7 lks. dist. mkd. T20S R11W S20 BT.

A Fir 30" dia., bears S.51°E., 20 lks. dist. mkd. T20S R11W S29 BT.

A Fir 24" dia., bears S.55°W., 6 lks. dist. mkd. T20S R11W S30 BT.

A Fir 40" dia., bears N.2°W., 14 lks. dist. mkd. T20S R11W S19 BT.

-----  
Survey by Ronald L. Durham - For: Menasha Corp. - March 1965 - C.S. File 51/311

-----  
Drive a 2" x 2½ ft. alum. pipe 2 ft. into the ground, from which

35" Fir bears S.51°E., 13.2 ft., orig. BT, now a stump with a face and an alum. tag.

24" Fir bears S.55°W., 4.0 ft., orig. BT, now a stump with visible scribe.

New BT:

44" Fir bears N.84°W., 20.6 ft. scribed S19 BT. (BT has a forest service tag and a new BLM tag.)

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - Sept. 19, 1968 - C.S. File 53/66-100

-----  
Found - 2" Pipe near section corner.

42" D.Fir stump, N.86°W., 20.6 ft. scribed S19 BT.

24" D.Fir now stump, S.55°W., 4.0 ft. scribe visible

30" D.Fir now stump, S.51°E., 13.2 ft. shows good scar.

Set Brass cap at cor. mkd:

County Surveyors Office

T 20 S R 11 W

S 19 | S 20

S 30 | S 29

1968

New Bearing Objects:

¾" Iron rod, North 15.0 ft.

¾" Iron rod, North 10.0 ft.

2" Pipe S.31°W., 0.9 ft.

This corner lies North of flat bench approx. 100.0 ft.

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by John Minor - For: Menasha Corp. - Feb. 1993 -  
M 116-56

-----  
Found - 2" Alum. pipe, SW. 0.7 ft. from ground, 3/4" Iron  
pipe with DCSO brass cap 8" above ground.  
41" D.Fir stump S.62°E., 13.7 ft.  
52" D.Fir stump N.80°W., 19.8 ft.  
3/4" Iron rod N.4°E., 9.8 ft.  
3/4" Iron rod N.3°E., 15.1 ft.  
New BTs -19" Hemlock S.62°W., 31.1 ft. scribed S19 T20S R11W  
BT.  
8" Spruce N.7°W., 7.5 ft. scribed S20 T20S R11W BT.

Fd. ok by Troy J. Rambo - Oct. 1998 - M 131-9.