

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 154)

Set a post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on W. face; from which
 An Elder 3" dia., bears N.27°E., 17 lks. dist. mkd. 1/4 S BT
 An Elder 3" dia., bears S.45°W., 12 lks. dist. mkd. 1/4 S BT

Survey by Ronald L. Durham - For: Menasha Corp. and U.S. Plywood - 1966-67 (Filed May 1968) - C.S. File 55/65 and M 35-74

At the midpoint on W. line of Sec. 20, I set a 3" Post for 1/4 corner, from which
 24" Spruce bears N.65°W., 19.8 ft.
 12" Spruce bears N.26°E., 1.5 ft.
These trees face, but not scribed. At a later date, I will scribe the BTs and set more durable monument.

Fd. OK, Aug. 2, 1977 - DCSO, L. Monrean - C.S. File 59/38

Survey by John Minor - For: Menasha Corp. - Feb. 1993 - M 116-56

Set 1" x 30" I.P. with 2" Brass cap stamped T20S R11W 1/4 S19 S20 1993 LS 2052.
New BTs -11" Spruce S.39°E., 0.1 ft. scribed 1/4 S20 BT.
 14" Spruce S.6°W., 13.8 ft. scribed 1/4 S19 BT.
 11" Spruce N.38°W., 19.3 ft. scribed 1/4 S19 BT.
 8" D.Fir N.76°E., 23.0 ft. scribed 1/4 S20 BT.

Found OK by B. Bacon, Sept. 2002 - M141-10