

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 154)

Set a post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 17, 18, 19 and 20, mkd. T20S S17 on NE.; R11W S20 on SE.; S19 on SW.; S18 on NW. faces, with 3 notches on S. and 5 notches on E. edges; from which

A Spruce 15" dia., bears N.30°E., 76 lks. dist. mkd. T20S R11W S17 BT.

An Alder 30" dia., bears S.89°E., 56 lks. dist. mkd. T20S R11W S20 BT.

An Alder 24" dia., bears S.4°W., 79 lks. dist. mkd. T20S R11W S19 BT.

An Alder 30" dia., bears N.87½°W., 46 lks. dist. mkd. T20S R11W S18 BT.

Survey by John Minor - For: Menasha Corp. - Feb. 1993 - M 116-56

Found - 3/4" Iron pipe 1.5 ft. above ground.
35" Spruce stump N.30°E., 49.9 ft. to face, original scribe visible.

New BTs- 12" Alder S.27°E., 27.4 ft. to spike side center, bark scribed "S20 T20S R11W BT"

14" Alder S.6°W., 18.9 ft. to spike side center, bark scribed "S19 T20S R11W BT"

Brent Bacon - For: Menasha Forest Products Corp. - Sept. 2002 - M141-10

Found - 3/4" iron pipe
42" Spruce stump, N.30°E., 49.7 ft. visible scribe "S17T20SR11W"

15" Alder, S.3°E., 27.5 ft. visible scribe "S20T20SR11W" (Rec. S.27°E.)

15" Alder, S.10°W., 18.3 ft. visible scribe "S19T20SR11W" (Rec. S.6°W., 18.9 ft.)

New BT - 29" Fir, N.79°W., 59.0 ft. scribed "T20SR11WS18BT"