

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 32; and 5, T21-11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 116)

-----  
A Cedar 36" dia., which I marked  $\frac{1}{4}$  S on N. side, for  $\frac{1}{4}$  sec. cor.; from which

An Alder 14" dia., bears S.53°E., 34 lks. dist. mkd.  $\frac{1}{4}$  SBT

A Spruce 10" dia., bears N.36°E., 12 lks. dist. mkd.  $\frac{1}{4}$  SBT

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - R.B. Kimberling; P.L. Earle; S.J. Flause, crew - April 19, 1978 - C.S. File 59/46-30

-----  
Set a 1" x 36" I.P. with brass cap set 6" above ground in a 30" mound of stone and mkd: Douglas County Surveyor 1978

T 20 S R 11 W

1/4 S 32

S 5

T 21 S R 11 W

BTs: A 9" Spruce bears S.14°E., (55°@+25°) 49.8 ft. I double blaze and scribe  $\frac{1}{4}$  S5 CS BT.

A 7" D.Fir bears N.20°E., (69.4@+35°) 56.8 ft. I double blaze and scribe  $\frac{1}{4}$  S32 CS BT.

Corner is 5 ft. North of a westerly stream.