

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 148)

-----  
Set a sandstone, 9x8x7 ins., 6" in the ground, mkd. ¼ on N. face, for ¼ sec. cor.; and raised a mound of stone, 1½ ft. high, 2 ft. base, alongside; pits impracticable.

Survey by Glenn S. Baughman - For: Siuslaw National Forest - April 1970 - C.S. File 55/147-1 and M 39-48

-----  
No evidence of original survey found. Prorated corner.  
Set 2" x 30" galv. Iron pipe with a brass cap 24" in the ground mkd:

¼ Cor.  
T20S R11W  
¼ S 29  
S 32  
1970 LS 536

From the pipe monument, I marked new BTs:

23" Hemlock bears S.3°W., 22.4 ft.

21" Hemlock bears N.25°30'E., 44.3 ft.

Tony Hostetter - For: Rosboro LLC Co. - April 2008 - M155-72

-----  
Found - 2" iron pipe w/brass cap as set by Baughman in 1970.  
Both BTs are rotten stumps (M39-48)

New BTs- 15" fir, scribed "S32 ¼ BT" bears S.38°E., 13.9 ft. to spike.

13" fir scribed "S32 ¼ BT" bears S.12°W., 7.9 ft. to spike.

15" fir, scribed "S29 ¼ BT" bears N.41°W., 8.9 ft. to spike.

30" spruce scribed "S29 ¼ BT" bears N.02°W., 30.5 ft. to spike.