

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 152)

-----  
Set a post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face; from which  
A Maple 6" dia., bears N.9°E., 7 lks. dist. mkd. 1/4 S BT.  
A leaning Maple 7" dia., bears S.34°W., 8 lks. dist. mkd. 1/4 S BT.

Survey by Ronald L. Durham - For: Menasha Corp. and U.S. Plywood - 1966-67 (filed May 1968) - C.S. File 55/65 and M 35-74

-----  
The South line of the section was surveyed a few years ago by Gleason and Lamb and subsequently the S 1/4 corner and the E 1/16 corner on that line were established.  
At the S 1/4 corner, I Set a 2" alum. pipe, from which  
A 16" Hemlock bears N.38°30'W., 37.2 ft. scribed 1/4 S BT. (tagged)  
Leitel Creek Road bears West 100 ft. dist. approx.

Brent Bacon - For: Menasha Forest Products Corp. - Sept. 2002 - M141-10

-----  
Found - 2" alum. pipe.  
New BTs- 12" Spruce, N.17°E., 53.8 ft., scribed "1/4S20BT"  
18" Alder, S.21°E., 83.7 ft., scribed "1/4S29BT"  
14" Spruce, S.88°W., 9.1 ft., scribed "1/4S29BT"  
20" Fir, N.20°W., 38.3 ft., scribed "1/4S20BT"  
Road bears East approx. 115 ft.  
No evidence of rec. 16" Hemlock BT.

Fd. Alum. pipe & BTs Tony Hostetter - April 2008 - M155-72