

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 155)

Set a post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd. 1/4 S on N. face; and raised a mound of stone, 1 1/2 ft. high and 2 ft. base, alongside; pits impracticable.

Survey by Warren D. Hootman - For: Coos Bay Pulp Corp. - July 1, 1959 - C.S. File 51/29 and M 15-22

Drive a Pipe, and scribe:
Hemlock 24" DBH, bears S.16°00'W., 11.0 ft.
Spruce 24" DBH, bears N.52°00'E., 23.1 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - Sept. 22, 1969 - C.S. File 53/66-24

Found - No trace of Iron pipe or NE BT. (Due to corner falling in log landing)
24" Hemlock now stob, S.16°W., 11.0 ft. scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 20 S R 11 W
1/4 S 17
S 20
1969

Steel fence post set alongside.
New Accessories:

3/4" Iron rod bears North, 20.0 ft.
8" Hemlock S.26°E., 53.1 ft. mkd. "1/4 S20 CS BT"

Brent Bacon - For: Menasha Forest Products Corp. - Sept. 2002 - M141-10

Found - 1" iron pipe with 2 1/2" brass cap, mkd: "T20S R11S 1/4 S17 S20 1969"
23" Hemlock, S.24°E., 54.0 ft., healed face (rec. S.26°E., 53.1 ft.)

3/4" iron rod, bears North 20.0 ft.
New BTs- 8" Cedar, N.52°E., 10.9 ft., scribed "1/4S17BT"
12" Fir, S.51°W., 12.2 ft., scribed "1/4S20BT"