

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 158)

-----  
Set a post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., mkd. 1/4 S on North face, from which

A Fir 5" dia., bears S.84 1/2°W., 51 lks. dist. mkd. 1/4 S BT

A Spruce 12" dia., bears N.41°W., 50 lks. dist. mkd. 1/4 S BT.

J. Gabriel's house bears N.45°E., about 3.00 chs. dist.

J. W. Cole, County Surveyor - Wit: Wallace Smiley and Mailland Smiley - May 26, 1923 - C.S. File 1/35

-----  
I renewed this corner from the original BTs, both of which are alive and standing and check closely.

I chopped open the Fir BT and the scribe marks were plainly visible.

I set a 2" x 60" Iron pipe for corner.

Survey by Warren D. Hootman - For: Coos Bay Pulp Corp. - July 1, 1959 - C.S. File 51/29 and M 15-22

-----  
1/4 Corner is witnessed by the stump and felled D.Fir BT.

New BTs -Alder 26" DBH, bears S.55°00'E., 46.8 ft.

Alder 9" DBH, bears N.29°00'E., 13.7 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - Sept. 23, 1969 - C.S. File 53/66-11

-----  
Found - 1923 2" Iron pipe very badly rusted.

26" now 26" Alder, S.55°E., 46.8 ft., scribe visible.

9" now 13" Alder N.29°E., 13.7 ft. scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S R 11 W

1/4 S 8  
S 17

1969

New BTs -13" Hemlock S.85°W., 16.7 ft. mkd. "1/4 S17 CS BT"

14" Spruce N.77°W., 49.0 ft. mkd. "1/4 S8 CS BT"

Kris DeGroot - For Siuslaw National Forest - 7/2008 - M157-1

-----  
Found - 1 1/4" IP by Powell in 1969, firmly set, projecting 12" above the ground, with a 2 1/2" BC (properly) mkd.

From which an orig. BT by Theil in 1891:

A rotted fir stump bears S.84°30'W., 33.7 ft.

continued next page

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BTs by Hootman in 1959  
A 24" alder bears N.27°45'E., 13.9 ft. with healed blaze. (Rec. N.29°E., 13.7 ft.)  
A 26" rotted alder stump bears S.54°15'E., 46.8 ft. (Rec. S.55°E.)  
And bearing trees by Powell in 1969  
A 33" spruce bears N.77°45'W., 49.2 ft. with a healed blaze. (Rec. N.77°W., 49.0 ft.)  
A 36" hemlock bears S.88°W., 16.3 ft. with a healed blaze. (Rec. S.85°W., 16.7 ft.)  
New BT - A 8" spruce bears S.61°E., 34.8 ft. Scribed "¼ S17 BT".  
Also found a rusted 2" iron pipe by Cole in 1923 per C.S. File 1/35 set alongside.

Fd. Ok by Troy Rambo, 11/2011 - M163-8