

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 161-2)

Set a post 3 ft. long, 3" sq., 24" in the ground, on top of ridge, for 1/4 sec. cor., mkd. 1/4 S on N. face; from which
A Fir 15" dia., bears N.18°E., 33 lks. dist. mkd. 1/4 S BT.
A Fir 36" dia., bears S.13°W., 39 lks. dist. mkd. 1/4 S BT.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Sept. 10, 1957 - C.S. File 42/305

Found - Stump of the orig. BT, scribing is barely visible on the Sec. 8 BT and no scribing is apparent on the remains of the Sec. 5 BT.

I RESET the corner from these BTs at the original distances, which agree. This corner lays on top of a ridge as called for in the orig. notes.

Set 1" x 36" galv. Iron pipe, from which
An Alder 11" DBH bears N.41°00'E., 3.0 ft.
An Alder 9" DBH bears S.82°00'E., 4.4 ft.

Fd. OK, June 25, 1969 by DCSO, V. Tracy - C.S. File 53/66-103

Survey by Tom McCullough - For: U.S. Forest Service - Feb. 1970 - C.S. File 55/142-3

Reestablished by Hootman OLS 399 in 1957.

Found - 1" Iron pipe, from which
12" Alder bears N.41°E., 3.0 ft. scribing visible, has FS tags.
10" Alder bears S.82°E., 4.4 ft. scribing visible, has FS tags. (Doug. Co. tags)

Set 2" x 30" Iron pipe with brass cap mkd: T 20 S R 11 W
5
8
1970
650

Set 2 fence posts ± 5 ft. East facing South
± 5 ft. South facing East.

Fd. OK, Dec. 23, 1987 by D. Baker - M 105-40