

PRIMARY CORNER DESCRIPTION Sec Cor for 28, 29, 32 and 33

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 137)

 A Hemlock 8" dia., which I marked T20S S28 on NE.; R11W S33 on SE.; S32 on SW.; S29 on NW. sides, with 1 notch on S. and 4 notches on E. sides, for cor. to secs. 28, 29, 32 and 33, from which

A Spruce 24" dia., bears N.60°E., 60 lks. dist. mkd. T20S R11W S28 BT.

A Fir 48" dia., bears S.46°E., 9 lks. dist. mkd. T20S R11W S33 BT.

A Hemlock 15" dia., bears S.13°W., 59 lks. dist. mkd. T20S R11W S32 BT.

A Hemlock 8" dia., bears N.66½°W., 24 lks. dist. mkd. T20S R11W S29 BT.
 May 26, 1892

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Sept. 1964 - C.S. File 53/66-55

 Found - 48" old Fir stump, S.46°E., 6.0 ft., opened and found good scribing "B".

Rotten Spruce stump, N.60°E., 39.6 ft., too far gone to find scars, scribing.

Rotten remnants of Hemlock stump, S.13°W., 37 ft. (not 38.9 ft.)

No trace of corner tree or NW BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S R 11 W

S29 | S28

S32 | S33

1964

New BTs -10" D.Fir N.14°W., 11.0 ft. mkd. T20S R11W S29 CS BT

8" D.Fir N.17°E., 12.4 ft. mkd. T20S R11W S28 CS BT.

13" D.Fir S.9°W., 18.5 ft. mkd. T20S R11W S32 CS BT.

11" D.Fir S.69°E., 33.0 ft. mkd. T20S R11W S33 CS BT

Fd. OK, May 27, 1980 by E. Alvarado - C.S. File 61/6-51

Survey by Ronald Stuntzner - For: Siuslaw National Forest - Oct/Nov. 1981 - M 91-53

 Found - Original Corner, with 1964 DCSO brass cap, properly marked.

Rotted stump, (rec. Spruce) bears N.60°E., 39.6 ft. No scribes visible.

48" Fir stump bears S.46°E., 6.0 ft., barely visible arc scribing.

(Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec Cor for 28, 29, 32 and 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Rotted Hemlock remains as per 1964, bears S.13°W., 37.0 ft. (Rec. 38.9 ft.)
8" D.Fir, now down, bears N.17°E., 12.4 ft. visible scribes.
11" D.Fir now 12", bears S.69°E., 33.0 ft. healed face.
13" D.Fir now 20" bears S.9°W., 18.5 ft. healed face.
10" D.Fir bears N.14°W., 11.0 ft. healed face.
New BT - 16" D.Fir bears N.32°E., 35.8 ft. scribed "T20S R11W S28 BT"

Fd. BC & BTs (BTs now stumps) Tony Hostetter - April 2008 - M155-72