

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 140)

 Set a post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 16, 17, 20 and 21 mkd. T20S S16 on NE.; R11W S21 on SE.; S20 on SW.; S17 on NW. faces, with 3 notches on S. and 4 notches on E. edges; from which

A Spruce 12" dia., bears N.26°E., 63 lks. dist. mkd. T20S R11W S16 BT.

A Fir 36" dia., bears S.46°E., 28 lks. dist. mkd. T20S R11W S21 BT.

A Vine Maple 4" dia., bears S.20°W., 30 lks. dist. mkd. T20S R11W S20 BT.

A Vine Maple 4" dia., bears N.44°W., 24 lks. dist. mkd. T20S R11W S17 BT.

Survey by Warren D. Hootman - For: Coos Bay Pulp Corp. - July 1, 1959 - C.S. File 51/29 and M 15-22

 Set by proportion 5233.5 ft. South of the Sec. Cor. common to Secs. 17, 18, 19 and 20 and mark the following BTs:

Hemlock 24" DBH, bears S.34°00'E., 28.5 ft.

Cedar 18" DBH, bears S.60°00'W., 69.2 ft.

Maple 16" DBH, bears N.41°00'E., 34.3 ft.

Hemlock 20" DBH, bears N.29°30'W., 50.6 ft.

The 20" Hemlock and the Cedar are located on the West bank of a creek which flows NE.

Fd. OK, 1966-1967 by R. Durham - M 35-74; C.S. File 55/65

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - Sept. 24, 1969 - C.S. File 53/66-15

 Found - No record of any corner monument.

24" Hemlock, now stump, S.34°E., 28.5 ft. scribe visible.

18" Cedar, now stump, S.73°W., (Rec. S.60°W.) 69.2 ft., scribe visible.

16" Maple, now down, N.41°E., 34.3 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S R 11 W

S 17 | S 16

S 20 | S 21

1969

(Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

New BT - 30" Hemlock stump, N.72°E., 45.7 ft. scribed T20S R11W S16 CS BT. Stump is on top small ridge running N.
This corner lies in clear-cut on very steep NW. slope, about 50 ft. East of ravine.

Brent Bacon - For: Menasha Forest Products Corp. - Sept. 2002 - M141-10

Found - 1" iron pipe with 2½" brass cap, mkd: "T20S R11W S17 S16 S20 S21 1969"
21" Rotten Hemlock stump, N.72°E., 45.5 ft.
29" Rotten Hemlock stump, S.34°E., 28.5 ft., visible scribe.
29" Cedar stump, S.73°W., 68.2 ft. (rec. 69.2 ft.) visible scribe.
New BTs- 9" Alder, N.51°E., 6.0 ft., bark scribed "T20SR11WS16BT"
12" Alder, S.53°W., 13.3 ft., bark scribed "T20SR11WS20BT"

Kris DeGroot - For Siuslaw National Forest - 6/2008 - M146-80

Found - 1½" iron post by Powell, Douglas Co. Surveyor's Office in 1969 per C.S. File 53/66, firmly set, projecting 12" above the ground, with 2½" brass cap (PROPERLY) stamped
From which bearing trees by Hootman in 1959 per M15-22:
29" rotted hemlock stump bears S.36°45'E., 27.3 ft. with scribe marks visible (rec. S.34°E., 28.5 ft)
29" cedar stump bears S.75°15'W., 68.1 ft. with scribe marks visible (rec. S.60°W., 69.2 ft.).
And a bearing tree by DCSO in 1969:
21" rotted hemlock stump bears N.72°E., 45.9 ft. (Rec. 45.7 ft.)
And bearing trees by Bacon in 2002 per M141-10:
9" alder bears N.51°45'E., 6,3 ft. full bark scribing visible(rec. N.51°E., 6.0 ft.).
12" alder bears S.54°15'W., 13.3 ft. full bark scribing visible (rec. S.53°W.).
New - 5/8"x 30" iron rod with PC bears S.45°15'37"E., 11.38 ft.
5/8"x 30" iron rod with PC bears N.52°29'00"W., 12.11 ft.

Fd. BC & accessories 11/2017 - C.S. 65/97-4 by R. Rice