

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4 of T21-11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 115)

Set a post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor., marked ¼ S on N. face; from which

A Fir 27" dia., bears S.51°W., 10 lks. dist. mkd. ¼ S BT.

A Vine Maple 4" dia., bears N.83°E., 25 lks. dist. mkd. ¼ S BT.

Survey by Ronald Stuntzner - For: Moore Mill & Lumber - Jan. 23, 1969 - C.S. File 55/103

Set by proportionate measurement. The ¼ corner had been searched for but not found.

Set 1" Iron pipe, from which

Bark scribed 32" Fir, N.50°W., 1.8 ft.

Scribed 42" Fir, N.82°E., 9.5 ft.

This corner is approx. 390 ft. East of the Noel Creek Road on a spur ridge.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Karen Cheney; Steve J. Flause, crew - June 15, 1977 - C.S. File 59/34-39

Found - A 1" Iron pipe at ¼ cor. by Stuntzner.

32" D.Fir bears N.50°W., 1.8 ft., tree bark scribed "S33 ¼"

42" D.Fir now 52" bears N.82°E., 9.5 ft. Tree has unhealed blaze scribed "S33 ¼".

Set a 1" x 30" I.Pipe with brass cap attached at ¼ corner as determined by Stuntzner, cap stamped: Douglas Co. Surveyor

T 20 S

1/4 S 33
 S 4 R11W
 1977

Set 1" I.P. along easterly edge of cap.

New BT - 48" D.Fir bears S.4½°W., 88.4 ft. Tree double blazed and scribed "¼ S4 CS BT"

Corner lies at NE corner of stand of timber.

Fd. OK May 20, 1980 by E. Alvarado - C.S. File 61/6-46