

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 141)

-----  
Set a post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face; from which  
    An Alder, 3" dia., bears N.84°W., 33 lks., mkd: ¼ S BT.  
    An Alder, 4" dia., bears S.32°E., 45 lks., mkd: ¼ S BT.

Kris DeGroot - For Siuslaw National Forest - 6/2008 - M146-80

-----  
Found - I find no remaining evidence of the orig. corner monument or accessories.

Set - At proportionate distance I set a 2½"x30" alum. post, 30" in ground with 3¼" alum cap stamped:

USDA FOREST SERVICE  
T20S R11W  
¼     S 16  
       S 21  
       2008  
       PLS 1941

New - 8" D.Fir bears N.18°45'E., 13.5 ft. scribed "¼ S16 BT"  
      11" D.Fir bears S.46°30'E., 11.8 ft. scribed "¼ S21 BT"  
      23" D.Fir bears S.55°45'W., 77.3 ft. scribed "¼ S21 BT"  
      11" D.Fir bears N.54°45'W., 34.3 ft. scribed "¼ S16 BT"