

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 143)

Set a post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N. face; from which

A Hemlock 12" dia., bears N.12 3/4°E., 12 lks. dist. mkd. ¼ S BT.

A Hemlock 8" dia., bears S.70½°W., 39 lks. dist. mkd. ¼ S BT.

Survey by Ronald E. Stuntzner - For: U.S. Forest Service - April 1975 - M 55-76

Found - Orig. 8" Hemlock now 26" stump with "¼" scribe mark, S.70½°W., 25.7 ft.

Set 2" Brass cap and I.P. for ¼ cor. mkd. "T20S R11W ¼ S9 S16 PE 6245 1975".

New BTs -10" Fir S.73°E., 36.2 ft. mkd. ¼ S16 BT.

10" Hemlock N.45°W., 52.8 ft. mkd. ¼ S9 BT.

FD. BC & 5 BTs by K. DeGroot, 6/2008 - M146-80