

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 91)

-----  
Set post in Alder flat, for corner of secs. 33, 34, 27 and 28, from which

- An Alder 14" dia., bears N.83°W., 20 lks.
- An Alder 24" dia., bears S.60°E., 6 lks.
- An Alder 18" dia., bears N.50°E., 66 lks.
- A Vine Maple 4" dia., bears S.32°W., 13 lks.

Fd. and used in GLO survey by Wm. Thiel, under Contract #567, dated Feb. 12, 1981 - (DCSO records, Vol. 1 Pages 123-124)

Survey by Ronald E. Stuntzner - For: Siuslaw National Forest Oct/Nov. 1981 - M 91-53

-----  
Found - Original NE BT and re-established orig. corner. Set Alum. cap and alum. pipe mkd. "T20S R11W S28 S27 S33 S34 1981 PLS 1342", from which

- 16" now 31" orig. Alder bears N.50°E., 43.6 ft. visible partial bark scribes.
- New BTs -14" D.Fir bears S.67°E., 84.7 ft. scribed T20S R11W S34 BT.
- 53" W.R. Cedar bears S.53°W., 78.4 ft. scribed T20S R11W S33 BT.
- 18" Alder bears N.46°W., 43.2 ft. bark scribed T20S R11W S28 BT.

Corner position falls on Alder flat as orig. called. Calls to N., S., E., and West checked with old blazes.