

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 124)

-----  
Set a post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face; from which

An Alder 4" dia., bears N.27°E., 27 lks. dist. mkd. ¼ S BT

An Alder 3" dia., bears S.49°W., 15 lks. dist. mkd. ¼ S BT

Survey by Ronald E. Stuntzner - For: Siuslaw National Forest Oct/Nov. 1981 - M 91-53

-----  
No evidence of original corner found.

Set Alum. cap and alum. pipe at proportioned distance mkd. "T20S R11W ¼ S28 S27 1981 PLS 1342".

New BTs -38" D.Fir bears S.57°W., 55.6 ft. scribed E ¼ S28 BT

12" Hemlock bears S.81°E., 37.0 ft. scribed W ¼ S27 BT.