

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 126-7)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 15, 16, 21 and 22, marked T20S S15 on NE.; R11W S22 on SE.; S21 on SW.; S16 on NW. face, with 3 notches on E. and S. edges; from which

- An Alder 4" dia., bears N.2°E., 20 lks. dist. mkd. T20S R11W S15 BT.
- An Alder 10" dia., bears S.84°E., 32 lks. dist. mkd. T20S R11W S22 BT.
- A Fir 48" dia., bears S.63½°W., 7 lks. dist. mkd. T20S R11W S21 BT.
- An Alder 8" dia., bears N.88°W., 51 lks. dist. mkd. T20S R11W S16 BT.

Warren D. Hootman - July 1959 - C.S. File 51/29 (Page 5 of 9)

-----  
Corner position is witnessed by the original D.Fir BT. This tree is bark scribed and bears several cruiser marks. This is the only evidence of the original corner witnesses. The corner lays on a rocky North face about 100 ft. from the spur we crossed to the East and about 150 ft. below the main divide. The area North and East has slid to bare rock, in the last year.

Ernesto R. Alvarado, USFS - Deputy, Douglas Co. Surveyors Office - Wit: Jill O'Neil - April 17, 1978 - C.S. 59/46-83

-----  
Found - Unrecorded 2" brass cap set by Dennis A. Crow, LS #845, marked "T20S R11W S16 S15 S21 S22 1973 845 LS".

16" Cedar with a dead top, bears N.8°W., 21.0 ft. with visible scribing mkd. "S15 BT"

60" D.Fir sawed off stump, bears S.69°W., 7.07 ft. with faded bark scribe visible, "BT T20 R11W" (the size of the loop on the "B" is one inch) Orig. BT.

Tags on the D.Fir stump indicate that it was visited by Bob B. from the Douglas County Forest Appraisal Dept., Oct. 23, 1953 and W. Camp from U.S. Plywood, July 23, 1965. Robert Ward, Land Surveyor for Champion International talked with Mr. Camp about the tag and the bark scribing since orig. notes did not mention scribing. Mr. Camp said that he found a number of BTs in the five mile area that were bark scribed instead of being blazed and scribed.

Set Brass cap at corner mkd:

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas County Surveyors Office  
T 20 S R 11 W  
S 16 | S 15  
S 21 | S 22  
1978

New Accessories:

- Unrecorded brass cap, N.89°30'E., 2.45 ft.
- 6" Alder bears S.86°30'E., 18.20 ft. bark scribe "T20S R11W S22 CS BT".
- 60" D.Fir sawed off stump, bears S.63°30'W., 4.62 ft. rescribed "CS BT" on a lower blaze.
- 16" Cedar bears N.16°E., 19.8 ft. rescribed "CS" below old scribing.

How to reach, From road junction of 1909.3 and 1901.1, take the NE spur road to the forest cat road on Left side of road; then follow the cat road past the landing to a location poster on the Left side; then go N.24°E. about 75 ft. to the corner.

Ronald L. Rice, Ward NW - For: Pacific West Timber LLC & US Forest Service - 5/2005 - M 147-53

-----  
Found - County Surveyors 2½" brass cap dated 1978 with the following accessories;  
Unrecorded brass cap bears N.89°30'E., 2.45'  
12" alder staub bears S.86½°E., 18.2' - face visible  
60" D.Fir stump bears S.63½°W., 4.6' - scribing visible  
22" cedar bears N.16°E., 19.8' - healed face  
New BTs- 10" D.Fir bears S.64°E., 40.4' - blazed, scribed T20S R11W S22 BT.

Kris DeGroot - For Siuslaw National Forest - 6/2008 - M146-80

-----  
Found - 1½" iron post by Alvarado, DCSO in 1978 per C.S. File 59/46, now firmly set and projecting 12" above the top of a new 48" dia. x 48" high mound of stone with a 2½" brass cap (properly) stamped:  
From which an original BT by Thiel in 1891:  
60" D.Fir stump bears S.63°30'W., 4.6 ft., with illegible scribe marks visible on rotten blaze.  
BTs by Alvarado in 1978 per C.S. File 59/46  
A 22" cedar bears N.16°E., 19.8 ft. with healed blaze  
BT by Rice in 2005 per M147-53:  
A 11 " D.Fir bears S.64°E., 40.4 ft. with pitched over blaze.

continued next page

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A RM by Crow in 1973:  
A 1" iron pipe with a 2½" brass cap stamped "T20S  
R11W S16 S15 S21 S22 1973 845LS" bears  
N.89°30'E., 2.45 ft.  
New BTs- A 8" D.Fir bears S.11°W., 24. 6 ft. scribed "T20S  
R11W S21 BT".  
A 9" D.Fir bears N.54°30'W., 66.5 ft. scribed "T20S  
R11W S16 BT".