

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 129-130)

Set a post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 3, 4, 9 and 10, marked T20S S3 on NE.; R11W S10 on SE.; S9 on SW.; S4 on NW. face, with 5 notches on S. and 3 notches on E. edges; from which

A Fir 30" dia., bears N.3½°E., 110 lks. dist., mkd. T20S R11W S3 BT.

A Fir 5" dia., bears S.53°E., 114 lks. dist. mkd. T20S R11W S10 BT.

A Fir 36" dia., bears N.7°W., 95 lks. dist. mkd. T20S R11W S4 BT.

A Chitten 3" dia., bears S.52°W., 5 lks. dist. mkd. T20S R11W S9 BT.

May 19, 1892

Survey by Ronald E. Stuntzner - For: U.S. Forest Service - April 1975 - M 55-76

Found - Orig. 30" Fir, now 44", N.3½°E., 70.2 ft.
Orig. 36" Fir, now 52", N.7°W., 60.7 ft.**

Set 2" Brass cap and Iron pipe for corner mkd: "T20S R11W S4 3 9 10 PE 6245".

New BTs -26" Fir S.31°E., 3.8 ft. mkd. T20S R11W S10 BT.

26" Fir S.15°W., 26.1 ft. mkd. T20S R1W S9 BT.

****Note - The dist. to the fd. orig. NW BT was corrected on 10/29/2003 - was typed as 69.7 ft. but should be 60.9 ft. JC**

Ronald Rice, Ward NW INC. - 10/23/2003 - C.S. File 65/48-34

Found - 2¼" iron pipe with brass cap dated 1975
50" Fir bears N.2°E., 69.7' bark scribing visible
60" Fir bears N.7½°W., 59.2' healed face.
32" Fir bears S.27°E., 3.5' healed face.
34" Fir bears S.16°W., 26.0' healed face.

Set - 4" post adjacent to corner.

Note - All BTs have red painted band & face with yellow BT tag.