

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 92)

-----  
Set ¼ sec. post, from which  
    An Alder 5" dia., bears N.48½°E., 13 lks. dist.  
    A Chittewood 5" dia., bears S.65½°W., 23 lks. dist.

Survey by Ronald E. Stuntzner - For: Siuslaw National Forest  
Feb. 15, 1982 - M 91-54 A & B

-----  
No evidence of original corner found.  
Set alum. cap rock monument at proportioned mid-point, mkd.  
"T20S R11W 1/4 S27 S34 1981 PLS 1342".  
New BTs -34" W.R. Cedar bears S.64°E., 80.8 ft. scribed N ¼  
    S34 BT.  
    54" D.Fir with 32 ft. schooledmarmed stem bears  
        S.68°E., 78.8 ft., not tagged.  
    26" Maple bears N.7°W., 99.3 ft. scribed S ¼ S27 BT.