

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 125)

-----  
Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., mkd. ¼ S on N. face; from which

An Alder 24" dia., bears N.87°E., 97 lks. dist. mkd. ¼ S BT.

An Elder 3" dia., bears S.36°W., 4 lks. dist. mkd. ¼ S BT.

Survey by Ronald E. Stuntzner - LS #1342 - For: Siuslaw National Forest - Oct/Nov. 1981 - M 91-55

-----  
No original evidence found. Corner as proportioned falls on South edge of creek.

Set Alum. pipe with alum. cap at proportioned North ¼ mkd. "T20S R11W ¼ S22 S27 1981 PLS 1342".

New BTs -8" D.Fir bears N.51°E., 33.9 ft. scribed "T20S R11W S22 ¼ BT"

10" Alder bears S.72°W., 24.0 ft. bark scribed "T20S R11W S27 N ¼ BT"

50" D.Fir snag bears S.23°E., 25.4 ft. scribed "T20S R11W S27 N 1/4 BT". Dist. to tag.

Fd. OK, Nov. 1991 by L. Roberts - M 114-29