

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 127)

-----  
Set a post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N. side; from which

A Hemlock 3" dia., bears S.65½°E., 37 lks. dist. mkd. ¼ S BT.

An Alder 4" dia., bears N.54°W., 85 lks. dist. mkd. ¼ S BT.

Survey by Ronald E. Stuntzner - For: U.S. Forest Service - Aug. 28, 1978 - M 73-7

-----  
Set Brass cap with iron pipe mkd. "T20S R11W ¼ S15 S22 1978 PLS 1342" for S ¼ corner Sec. 15, from which

34" D.Fir bears N.84°E., 67.22 ft.

12" R.Alder bears S.2°W., 37.67 ft.

48" D.Fir snag, North 12.2 ft.

36" D.Fir stump bears S.37°E., 31.95 ft.

Fd. OK, Nov. 1991 by L. Roberts - M 114-29

Fd. Ok by Ronald Rice - May 2005 - M147-53

Ron Rice - for: Campbell Global - May 2017 - C.S. 65/96-10

-----  
Found - 1978 brass cap per M73-7 with the following accessories:

39" D.Fir bears N.84°E., 67.2' - healed face

20" Alder bears S.2°W., 37.7' - bark scribing visible

48" D.Fir snag bears N.0°W., 12.2' - no marks.

36" D.Fir stump bears S.37°E., 32.0' - no marks

Carsonite post adjacent to corner