

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 128-129)

Set a post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on N. face; from which
An Alder 15" dia., bears S.69 1/2°E., 38 lks. dist. mkd. 1/4 S BT.
A Fir 30" dia., bears N.58°W., 45 lks. dist. mkd. 1/4 S BT.

Fd. and used in HES #190 survey by Frederick W. Rase, under Special Instructions dated Feb. 12, 1916 (DCSO records, Vol. 1 Page 171 (and duplicate Pg. #12058 Vol. 28)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - Sept. 25, 1969 - C.S. File 53/66-28

Found - Orig. 30" D.Fir, now stump, N.58°W., 29.7 ft. faint bark scribe.
No trace of Alder bearing tree.
Set Brass cap at cor. mkd: County Surveyors Office
T 20 S R 11 W
1/4 S 10
S 15
1969

Steel fence post alongside.
New BTs -48" D.Fir N.88°E., 178.8 ft. mkd. "1/4 S10 CS BT"
48" D.Fir S.64°E., 184.0 ft. mkd. "1/4 S15 CS BT"
Corner lies in fairly flat area in old unit.

April 1970, Tom McCullough set a fence post with sign ± 5 ft. North facing West. C.S. File 55/148-1

Douglas County Surveyors Office - Randall Smith, Deputy; Terrie Frannsen, crew - May 15, 1992 - C.S. File 64/26-7

Found - 2 1/2" dia. 1969 DCSO brass cap on 1 1/2" O.D. Iron pipe protruding 2" above ground.
30" now 72" dia. 6 ft. high D.Fir stump, no bark scribing visible, bears N.58°W., 29.7 ft. (Orig. BT) (agrees w/record)
48" now 43" dia. D.Fir with a fully healed single blaze, bears N.88°E., 178.8 ft. (agrees w/rec)
48" now 46" dia. D.Fir with a fully healed single blaze, bears S.64°E., 184.0 ft. (agrees w/rec)

(Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

84" dia. 4 ft. high D.Fir stump with BT tag, with
faced bark, no scribing visible, tag says
"N.84°W., 15.1 ft." Stump bears S.80°E., 19.7 ft.
(Unrecorded BT)
New BTs -18" dia. Hemlock double blazed and scribed "¼ S10 CS
BT" bears N.78°W., 5.4 ft.
18" dia. D.Fir double blazed and scribed "¼ S15 CS
BT" bears S.41°E., 16.8 ft.

Fd. Ok by Ronald Rice - May 2005 - M147-53