

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 440560

PRIMARY CORNER DESCRIPTION SW Cor HES 190 on N-S Centerline S 10

Alias 938060 Description Cor #6 H E S #190
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey of HES #190 by Frederick W. Rase, under Special Instructions dated Feb. 12, 1916, surveyed Sept. 1916 - (DCSO records Vol. 28 Page(s) 12061)

Cor. No. 6 (100 ft. below top)
I destroy temporary stake and in its place
Set a Cedar post, 3 ft. long, 5" sq., 24" in the ground, over a stone mkd. with a cross, for 1/16 sec. cor. and cor. No. 6 of this survey, mkd. 1/16 on W. face and 6 HES 190 on side facing the claim; from which
 A Fir 8" dia., bears N.50°17'W., 17 lks. dist. mkd. X 6 HES 190 1/16 BT.
 A Fir 12" dia., bears N.65°00'E., 48 lks. dist. mkd. X 6 HES 190 1/16 BT.
Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.
No stone available for cor.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - April 1970 - C.S. File 53/66-5

Found - Remains of old Cedar post, in place.
 Orig. 12" now 20" Fir, alive, N.65°E., 31.7 ft., shows old scar and some more recent chopping, We tag.
 Orig. 8" dia., now 14" Fir, down, N.50¼°W., 11.2 ft., open and scribe visible on open blaze.
Set Brass cap at cor. mkd: County Surveyors Office
 T 20 S R 11 W
 N 1/16 | Cor.#6HES 190
 Sec.10
 1970
New BTs -24" Spruce S.36°W., 27.0 ft. mkd. "6 HES 190 N 1/16 S10 CS BT"
 14" D.Fir N.50°W., 33.8 ft. mkd. "6 HES 190 N 1/16 S10 CS BT"
This corner lies on very steep NE. slope, approx. 50 ft. West of small ravine, course North.

Fd. Ok by Ronald Rice - May 2005 - M147-53