

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 460560

PRIMARY CORNER DESCRIPTION S SE Cor HES #190 in NE ¼ Sec 10

Alias 938050 Description Cor #5 of H.E.S. #190
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO of H.E.S. Survey by Frederick W. Rase, Surveyor, under Special Instructions dated Feb. 12, 1916 - Surveyed Sept. 1916 - (DCSO records Vol. 28 Page(s) 12060-61)

Cor. No. 5 (190 ft. above cor. No. 4)
Set a basalt stone, 30x14x8 ins., 8" in the ground to bedrock over a stone mkd. with a cross, surrounded by mound of stone, for cor. No. 5 on this survey, mkd. 5 HES 190 on side facing the claim; from which

A Fir 8" dia., bears S.68°15'W., 26 lks. dist. mkd. X 5 HES 190 BT.

A Fir 12" dia., bears S.20°30'W., 23 lks. dist. mkd. X 5 HES 190 BT.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - April 1970 - C.S. File 53/66-4

Found - Mound of stone, probable corner stone, in place, no marks found.

Orig. 8" now 8" dead Fir snag, badly decayed, S.68¼°W., 17.2 ft., scribe "X5 HES 190 BT" visible on unhealed blaze.

Orig. 12" now 12" dead Fir, S.20½°W., 15.2 ft. scribed "X5 HES 190 BT" visible on unhealed blaze.

Set Brass cap at cor. mkd: County Surveyors Office
T 20 S R 11 W
5 _____ | HES 190
1970

New BTs -16" D.Fir N.88°E., 32.4 ft. mkd. "5 HES 190 CS BT"
16" D.Fir N.14°E., 29.1 ft. mkd. "5 HES 190 CS BT"

This corner lies on point of spur, sloping NW.