

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T21-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 1 Page(s) 84 (and duplicate page 1163))

Set post for corner to secs. 2, 3, 34 and 35, from which

An Alder 10" dia., bears S.8°W., 70 lks. dist.

A Willow 4" dia., bears N.15°W., 89 lks. dist.

An Alder 7" dia., bears N.70°E., 30 lks. dist.

An Alder 12" dia., bears S.4°E., 73 lks. dist.

Jan. 18, 1969

Survey by Bruce A. Shaner - For: Moore Mill & Lumber Co. -
RM 3-48 - July 1981

Set brass cap mkd. T20S R11W WM S34 S35 S2 S3 T21S RLS 430
1981, from which

26" W.Red Cedar, I scribed T20S R11W S35 BT, bears
N.89½°E., 146.0 ft.

28" Spruce, I scribed T21S R11W S2 BT, bears S.41°E.,
136.6 ft.

12" Alder, I bark scribed T21S R11W S3 BT, bears S.70°W.,
27.4 ft.

18" Alder, I bark scribed T20S R11W S34 BT, bears N.59°W.,
85.3 ft.

County monument "S-7" bears N.75°33'26.8"W., 996.92 ft.

Steel fence post alongside the set brass cap.