

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Henry W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 1 Page(s) 88)

-----  
Set post for ¼ sec. corner, from which  
An Alder 6" dia., bears S.44°W., 20 lks. dist.  
An Alder 12" dia., bears N.85°E., 83 lks. dist.

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 91)

-----  
The ¼ sec. post on line between secs. 34 and 35, from which  
An Alder 6" dia., bears S.44°W., 20 lks. dist.  
An Alder 12" dia., bears N.85°E., 83 lks. dist. (now down)

Survey by Ronald E. Stuntzner - For: Siuslaw National Forest  
Feb. 15, 1982 - M 91-54 A-B

-----  
No evidence of original corner found.  
Set alum. pipe with alum. cap at proportioned position mkd.  
"T20S R11W 1/4 S34 S35 1981 PLS 1342",  
from which  
22" D.Fir bears N.5°E., 33.3 ft. scribed W 1/4 S35 BT.  
22" D.Fir bears S.1°E., 21.4 ft. scribed W 1/4 S35 BT.  
23" D.Fir bears N.35°W., 19.8 ft. scribed E 1/4 S34 BT.

Fd. OK, Dec. 1990 - M 111-47 A-F