

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 92)

Set post on a small spur, close to rocky cliff, for corner to secs. 26, 27, 34 and 35, from which

A Chittewood 6" dia., bears N.6½°W., 80 lks. dist.
There is no other living tree in sight, no chance for any pits, as the rock is too close to the surface.

Nov. 26, 1879

Survey by Ronald E. Stuntzner - For: Siuslaw National Forest
Feb. 15, 1982 - M 91-54 A & B

Original calls checked, however, no orig. evidence found.
Set Alum. pipe with alum. cap at double proportioned section corner, mkd. "T20S R11W S27 S26 S34 S35 1981 PLS 1342".

New BTs -24" D.Fir bears N.54°E., 44.0 ft. scribed T20S R11W S26 BT.

20" Alder (poor condition) bears S.1°E., 34.5 ft. bark scribed T20S R11W S35 BT.

34" D.Fir bears S.70°W., 59.8 ft. scribed T20S R11W S34 BT.

40" D.Fir bears N.44°W., 29.0 ft. scribed T20S R11W S27 BT.

50" D.Fir remains (very old snag) bears S.16°E., 8.8 ft., not tagged.

Fd. OK, Dec. 1990 - M 111-47 A-F