

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 93)

Set post, close to trail to the Lake country, for corner of secs. 26, 27, 22 and 23; from which

A Chittewood 15" dia., bears S.43 3/4°E., 10 lks.

A Chittewood 15" dia., bears N.20°E., 18 lks.

An Alder 12" dia., bears S.44 1/2°W., 72 lks.

An Alder 24" dia., bears N.53°W., 140 lks.

Fd. and used in GLO survey by Wm. Thiel, under Contract #567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page 121)

Survey by Robert B. Ward, LS #1091 - For: Champion International - Sept. 1981 - C.S. File 58/260 and M 89-58

(Corner Report only - See C.S. File 58/260 for affidavit)

Found - 3 1/2" Iron cap on a 2 1/2" Iron pipe.

27" Alder bears S.34°0'W., 39.9 ft.

25" Hemlock bears N.31°0'E., 36.5 ft.

48" twin Alder bears N.1°0'W., 44.3 ft.

24" Alder stump bears S.48°0'E., 35.8 ft.

BT dates unknown.

Survey by Ronald Stuntzner - For: Siuslaw National Forest - Oct/Nov. 1981 - M 91-55

Found - Original corner position as per affidavit recorded in Vol. 318 Page 783, Douglas County Clerk Records. Affidavit also filed in County Surveyors records, C.S. 58/260

Steel cap 3" and 2 1/2" I.P. in concrete mkd. S22 S23 S27 S26.

23" Hemlock bears N.30°E., (Rec. N.28°E.) 36.8 ft.

16" Alder stump, rotted, bears S.46°E., 35.4 ft.

26" Alder bears S.34°W., 39.0 ft. bark scribed S27 BT. (Distance measurement to face)

18" twin trunk Alder bears N.3°W., 39.9 ft. bark scribed S22 BT.

New BT - 14" W.R. Cedar bears S.44°E., 120.7 ft. scribed S26 BT T20S R11W.

Fd. OK, Dec. 1990 - M 111-47 A-F

continued next page

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Jerry Estabrook - Crew: Patrick Coy, John Rondeau, and Daniel Tiemissen - 6/26/2022 - C.S. 65/111-7

Found - A 2½" galv. iron pipe with an iron cap marked
S22|S23 and established per CS 58-260.

S27|S26

BTs - A 39" Hemlock w/a healed face and tag bears N.31°E.,
36.5'.

A 36" Alder w/visible scribe and tag bears S.34°W.,
39.9'.

A 39" rotten alders windfall bears N.01°W., 44.3'.

BOs - A carsonite post bears N.0°W., 2.5'.

An angle iron post w/sign bears S.0°W., 4.0'.

New BTs- A 16" Alder, bark scribed "NW S26 BT" with x-chop
and tag bears S.78°E., 27.2' to a spike at side
center.

Locations & comments Lat. & Long. per GARMIN ETREX handheld

GPS N: 43°48'37.0" W: 123°59'11.5"

Compass declination: 18° east