

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 122)

An Alder 3" dia., which I marked ¼ S on W. face, for ¼ sec. cor., from which

An Alder 3" dia., bears S.5°W., 38 lks. dist. mkd. ¼ S BT

An Alder 2" dia., bears S.40°E., 96 lks. dist. mkd. ¼ S BT

Survey by Robert B. Ward, LS #1091 - For: Champion International - Sept. 1981 - C.S. File 58/260 and M 89-58

Found no trace of original corner.
Set 3½" USFS alum. cap on a 2½" x 30" alum. pipe at point of proportionate measure, from which

26" Hemlock bears N.62°23'W., 29.0 ft. (1981) scribed ¼ S22 BT.

20" Hemlock bears N.51°55'E., 33.1 ft. (1981) scribed ¼ S23 BT.

Fd. OK, Nov. 1991 by L. Roberts - M 114-29

Jerry Estabrook - Crew: Patrick Coy, John Rondeau, and Daniel Tiemissen - 6/26/2022 - C.S. 65/111-6

Found - A 2½" aluminum pipe w/an aluminum cap marked "USDA FOREST SERVICE T20S R11W ¼ S22|S23 1981 PLS 1091 UNLAWFUL TO DISTURB" and set per M89-58.

BTs - A 32" Hemlock w/a healed face and tag bears N.51°55'E., 33.1'.

A 39" Hemlock w/a healed face and tag bears N.62°23'W., 29.0'.

B0s - A carsonite post bears S.16°W., 1.7'.

A carsonite post bears N.90°W., 3.4'.

New BTs- A 12" Alder, bark scribed "W¼ S23 BT" with x-chop and tag bears S.10°W., 22.2' to a spike at side center.

Locations and comments: Lat. & Long. per GARMIN ETREX handheld GPS

N: 43°49'02.2" W: 123°59'11.2"

Compass declination: 18° East