

PRIMARY CORNER DESCRIPTION Sec Cor for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 122-123

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 14, 15, 22 and 23, marked T20S S14 on NE.; R11W S23 on SE.; S22 on SW.; S15 on NW. face, with 3 notches on S. and 2 notches on E. edges; from which

A Fir 30" dia., bears N.85°E., 19 lks. dist. mkd. T20S R11W S14 BT.

A Chittem 5" dia., bears S.35½°E., 40 lks. dist. mkd. T20S R11W S23 BT.

A Chittem 6" dia., bears S.32½°W., 12 lks. dist. mkd. T20S R11W S22 BT.

A Fir 36" dia., bears N.41°W., 14 lks. dist. mkd. T20S R11W S15 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Sept. 17, 1968 - C.S. 53/66-117

-----  
Found - 30" D.Fir, now stump, N.85°E., 12.5 ft. burnt face, "BT" visible, opened more for other scribe.  
36" D.Fir now stump, N.41°W., 9.2 ft., shows scar.  
Also, call on spring branch of 66.0 ft. South of corner fits very good.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S R 11 W  
S 15 | S 14  
S 22 | S 23  
1968

New BT - 60" D.Fir stump N.6½°E., 46.8 ft. mkd. T20S R11W S14 CS BT.

This corner lies in clear cut unit. 66.0 ft. North of spring branch. West to spring branch. 330.0 ft. approx. West of ridge top.

All stumps tagged on top and side.

Ernesto R. Alvarado, U.S. Forest Service - Deputy, Douglas Co. Surveyors Office - May 19, 1978 - C.S. File 60/11-10

-----  
Found - 2" brass cap 9 on a 1" pipe, firmly set mkd. County Surveyors Office 1968 S15 S14 S22 S23.

35" D.Fir stump bears N.85°E., 13.48 ft. scribing visible "1W". Orig. BT.

45" D.Fir stump bears N.39°W., 9.8 ft. Orig. BT.

60" D.Fir stump bears N.11°E., 46.94 ft. scribing visible "T20S R11W S14 CS BT"

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec Cor for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Reset County brass cap, N.41°30'E., 1.55 ft. to GLO calls, distance to original BT. I have previously discussed the resetting of the county cap with F.L. Ingram, County Surveyor.

New Bearing and distances:

45" D.Fir stump bears N.45½°W., 9.14 ft.

35" D.Fir stump bears N.88½°E., 12.54 ft.

60" D.Fir stump bears N.9°E., 45.68 ft.

Bearings are to visible scribing and distance are to the center of tree at its root crown.

Go on USFS Road 1908 (new 4811) 0.7 mile from road junction 2059 to location poster on right side of the road. Then take old spur to the landing. The corner lies approx. 250 ft. due North of the landing.