

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 134)

Set a post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face; from which

A Willow 4" dia., bears N.12°W., 39 lks. dist. mkd. ¼ S BT.

A Cedar 24" dia., bears S.27°E., 15 lks. dist. mkd. ¼ S BT

Survey by Donald Peel, LS #752 - For: Davidson Industries, Inc. - Dec. 11, 1981 - M 89-66

Position for ¼ corner is occupied by a 40" Fir, so I set a WITNESS corner S.0°32'50"W., 4.0 ft. from exact corner point. Set 1½" x 40" Iron pipe with brass cap mkd. "W.C.", from which

25" Fir bears S.54°E., 41.0 ft. scribed "X".

40" Fir bears S.77°W., 15.1 ft. scribed "X".

(Bearing and distances are from Witness Corner)

Fd. OK, May 1993 by D. Baker - M 118-6