

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 123)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor. mkd. ¼ S on N. face; from which

An Alder 3" dia., bears S.14°E., 29 lks. dist. mkd. ¼ S BT
A Hazel 3" dia., bears N.27°W., 41 lks. dist. mkd. ¼ S BT.

Survey by Robert B. Ward, LS #1091 - For: Champion International - Sept. 1981 - C.S. File 58/260 and M 89-58

Found no trace of original corner.

Set 2½" brass cap on a 2½" x 30" I.P. at point of proportionate measure, from which

27" Fir bears S.0°15'W., 45.8 ft. (1981) scribed ¼ S23 BT
51" Fir bears N.53°15'E., 27.2 ft. (1981) scribed ¼ S14 BT