

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #342, dated Oct. 6, 1879 (DCSO records Vol. 1 Page(s) 94)

-----  
Set ¼ sec. post, from which  
    An Alder 9" dia., bears N.2°E., 128 lks. dist.  
    A Cherry 8" dia., bears S.56½°W., 30 lks. dist.

Survey by Harvey Wilcox, LS #2244 - For: U.S. Forest Service - Dec. 1990 - M 111-47 A-F

-----  
Set 3" alum. cap mkd. U.S.F.S. on 2½" x 30" alum. pipe.  
From which  
    22" D.Fir, face scribed "E 1/4 S35 BT" tags and washer bears N.20°30'W., 61.0 ft. to side center of tree.  
    31" D.Fir, face scribed "W 1/4 S36 BT" tags and washer bears N.3°E., 21.25 ft. to side center.  
    31" D.Fir, face scribed "W 1/4 S36 BT" tags and washer bears S.45°E., 6.10 ft. to side center.  
    5 ft. high rock face, with P.K. nail and washer in the center of an "X", with tag, bears N.58°W., 18.60 ft.