

PRIMARY CORNER DESCRIPTION Sec. Cor. for secs. 25, 26, 35 and 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 94)

Set post for corner of secs. 36, 35, 26 and 25; from which
An Alder 8" dia., bears N.72°W., 28 lks.
An Alder 10" dia., bears N.53°E., 75 lks.
An Alder 12" dia., bears S.77½°E., 60 lks.
A Hemlock 6" dia., bears S.21°W., 10 lks.

Nov. 28, 1879

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 119)

The Sec. Cor., which is a post, 4" sq., mkd. T20S S25 on NE.; R11W S36 on SE.; S35 on SW.; S26 on NW. faces, with 1 notch on S. and E. edges, from which

An Alder 10" dia., bears N.53°E., 75 lks. dist. mkd. T20S R11W S25 BT.
An Alder 12" dia., bears S.77½°E., 60 lks. dist. mkd. T20S R11W S36 BT.
A Hemlock 6" dia., bears S.21°W., 10 lks. dist. mkd. T20S R11W S35 BT.
An Alder 8" dia., bears N.72°W., 28 lks. dist. mkd. T20S R11W S26 BT.

Survey by Harvey Wilcox - For: U.S. Forest Service - Dec. 1990 - M 111-47 A-F

Set 3" alum. cap mkd. "U.S.D.A. Forest Service" on 2½" x 30" alum. pipe, from which

38" D.Fir, face scribed "T20S R11W S25 BT" tags and washer bears N.25°15'E., 39.45 ft.
16" D.Fir, face scribed "T20S R11W S36 BT" tags and washer, bears S.76°30'E., 13.77 ft.
40" D.Fir, school marm, face scribed 'T20S R11W S26 BT" bears N.20°30'W., 3.12 ft.
Standard USFS disk mkd. "RM T20S R11W S26 S.83°11'E., 40.56' 1990 RLS 2244" bears N.83°11'W., 40.56 ft.

Distances are to side center of bearing trees.