

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 95-96)

Set ¼ sec. post, from which
A Fir 42" dia., bears N.16°W., 20 lks.
A Fir 36" dia., bears N.18°E., 46 lks.

Survey by Harvey Wilcox - For: U.S. Forest Service - Dec. 1990 - M 111-47 A-F

Found - Orig. Fir, rotten stump, bears N.16°W., 13.2 ft. to face.
Orig. Fir, rotten stump, bears N.18°E., 30.4 ft. to face.

Set 3" alum. cap on 2½" x 30" alum. pipe mkd. "USDA Forest Service", from which new BTs:

- 89" Fir, face scribed "W ¼ S25 BT", tags and washer, bears S.61°E., 37.89 ft.
- 40" Maple, face scribed "E 1/4 S26 BT", tags and washer, bears S.6°15'W., 26.61 ft.
- 27" Maple, face scribed "E ¼ S26 BT", tags and washer, bears N.86°15'W., 40.01 ft.
- 44" Fir, face scribed "W ¼ S25 BT", tags and washer, bears N.14°45'E., 48.31 ft.

All distances are to the side center of the bearing trees.