

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Wm. Thiel under Contract #342 dated Oct. 6, 1879 - (DCSO records Vol. 1 Page(s) 96)

Post for corner to secs. 25, 26, 24 and 23 is a Fir, 15" in dia., from which
 A Fir 12" dia., bears N.55°E., 12 lks.
 An Alder 8" dia., bears N.64°W., 54 lks.
 An Alder 4" dia., bears S.2°W., 223 lks.
 An Alder 9" dia., bears S.2½°E., 193 lks.

Fd. and used in GLO survey by Wm. Thiel under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page 120)

Survey by Robert B. Ward - For: Champion International - Sept. 1981 - C.S. File 58/260 and M 89-58

Found no trace of original corner.
Set 3" brass cap cemented in sandstone outcrop at point of proportionate measure, from which
 31" Fir bears S.39°30'E., 71.9 ft. (1981) scribed "T20S R11W S25 BT"
 53" Fir bears N.52°0'W., 28.9 ft. (1981) scribed "T20S R11W S23 BT"
 8" Fir bears N.64°0'E., 22.5 ft. (1981) scribed 'T20S R11W S24 BT"
 2 ft. wide sandstone ledge mkd. "X BO", bears S.70°15'W., 27.5 ft. (1981)

Fd. Ok 12/90 M 111-47 A-F