

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 120)

-----  
Set a post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., mkd. 1/4 S on W. face; from which  
A Cedar 10" dia., bears N.12°E., 44 lks. dist. mkd. 1/4 S BT  
A Vine Maple 3" dia., bears S.80°W., 42 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Sept. 1964 - C.S. File 53/66-71

-----  
Found - 30" Red Cedar N.12°E., 29.0 ft. previously opened, good scribing "BT".

Other BT not found.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S R 11 W

1/4 S23 | S24

1964

Rescribe-30" Red Cedar N.12°E., 29.0 ft. mkd. "1/4 S24 CS BT"  
New BT - 26" D.Fir S.41°E., 33.4 ft. mkd. "1/4 S24 CS BT". (49 ft. at 47° slope.)

Corner is in bottom of draw, approx. 10 ft. S. of stream line.

Found in good condition June 1969 by Prahar - C.S. File 55/117