

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 132)

Set a post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S on W. face; from which

A Fir 8" dia., bears S.63°E., 47 lks. dist. mkd. ¼ S BT.

A Fir 4" dia., bears S.10½°W., 62 lks. dist. mkd. ¼ S BT

Survey by Donald Peel - For: Davidson Industries, Inc. - May 6, 1983 - M 94-64 and C.S. File 58/274

Set 1½" x 36" Iron pipe with brass cap, from which

31" Fir, S.59°E., 32.2 ft.

39" Fir, N.15°W., 18.1 ft.

Survey by Donald Peel - For: Davidson Industries - Nov. 27, 1984 - M 97-64

AMENDED CORNER.

Set 1½" x 36" I.P. with brass cap, from which

37" Fir, S.81½°E., 62.6 ft.

31" Fir S.57½°W., 53.3 ft.

Position of cor. per M 94-64 bears South, 223.95 ft.