

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 119)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face; from which
A Cedar 36" dia., bears S.87°W., 24 lks. dist. mkd. 1/4 S BT
A Fir 24" dia., bears N.88°E., 16 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, Frank Jones, crew - Sept. 12, 1966 - C.S. File 53/66-99

Found - Orig. 36" now 48" Cedar S.87°W., 15.8 ft., previously opened and shows "1/4 S BT". Previous opened and shows scribe with approx. 70-75 years of overgrowth. Alive with top broken out.

Set Brass cap at cor. mkd: County Surveyors Office
T 20 S R 11 W

S 25
S 36
1966

New BTs -8" Hemlock N.69 1/2°W., 19.9 ft. mkd. 1/4 S25 CS BT.
18" R.Cedar S.61°W., 31.6 ft. mkd. 1/4 S36 CS BT.

This corner lies on top of small bluff approx. 35 ft. high on NE. slope 125 ft. West of creek, course SE.

Survey by Clyde F. Mulkins, LS #2006 - For: Coos Head Timber Co. - Nov. 1, 1982 - M 93-30 A-B

Found - 2" DCSO 1966 brass cap.
48" Red Cedar bears S.87°W., 15.8 ft. (Orig.)
12" Hemlock bears N.69°W., 19.9 ft.
24" Red Cedar bears S.61°E., 31.6 ft. (Rec. S.61°W.)

Fd. OK, Dec. 1990 - M 111-47 A-F