

PRIMARY CORNER DESCRIPTION Tsp cor for T19-11 & T19-10 S

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Contract 546, dated August 16, 1889 - (DCSO records Vol. 1 Page(s) 104-105)

Set a post 4½ ft. long, 5" sq., 24" in the ground, for cor. of Tps. 19 & 20., Rs. 10 & 11 W., marked T19S S31 on NE.; R10W S6 on SE.; T20S S1 on SW.; and R11W S36 on NW. faces, with 6 notches on each edge; from which

- A Cherry 5" dia., bears N.76°W., 18 lks. dist. mkd. T19S R11W S36 BT.
- A Fir 50" dia., bears S.46½°W., 45 lks. dist. mkd. T20S R11W S1 BT.
- A Fir 36" dia., bears N.77½°E., 29 lks. dist. mkd. T19S R11W S31 BT.
- A Cherry 5" dia., bears S.32½°E., 33 lks. dist. mkd. T20S R10W S6 BT.

Cor. Fd. in GLO survey by Wm. Thiel under Contract #567 dated Feb. 16, 1891 (DCSO records, Vol. 1 Pages 110-111)

Douglas County Surveyors Office - Bruce R. Rogers, Deputy; Mike Stone, crew - June 23, 1965 - C.S. File 53/66-137

Found - 50" Fir now snag, S.46½°W., 29.7 ft.
 36" Fir now snag, N.77½°E., 19.1 ft. (See affidavits for evidence of scribing)

Set Brass cap at cor. mkd: Doug. County Surveyors Office
 T 19 S
 R11W S 36 | S 31 R10W
 1965

New BTs -8" Alder S.36°W., 9.4 ft. mkd. T20S R11W S1 CS BT.
 12" Alder S.7°W., 16.9 ft. mkd. T20S R11W S1 CS BT.

BLM resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page 16297)

The cor. of Tps. 19 S., Rs. 10 and 11 W., perpetuated by Bruce Rogers, in 1965, monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd.: DOUG COUNTY SURVEYORS OFFICE
 T 19 S
 R 11 S 36 | S 31 R 10
 W 1965 W

from which the remains of the original bearing trees
(Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 678700

PRIMARY CORNER DESCRIPTION Tsp cor for T19-10 & T19-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 32" dia., bears N.77½°E., 29 lks. dist., no marks visible.
A Fir snag 54" dia., bears S.46½°W., 45 lks. dist., with opened blaze, no marks visible.
and bearing trees mkd. by Rogers
An Alder 15" dia., bears S.10 3/4°W., 25 lks. dist., with scribe marks R11W visible on partially healed blaze.
An Alder 12" dia., bears S.36 3/4°W., 14 lks. dist. with scribe marks 20S R11W BT visible on partially healed blaze.
No suitable trees available within limits in secs. 31 and 36.

Fd. OK, Nov. 1984 by D. Peel - M 97-64