

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor Sec 36 (SE Tsp cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 1 Page(s) 86)(and duplicate on Pg. 1167)

Set post for corner to Townships 20 and 21 South, Ranges 10 & 11 West; from which

- An Alder 5" dia., bears N.11°W., 28 lks. dist.
- An Alder 4" dia., bears N.18°E., 25 lks. dist.
- An Alder 13" dia., bears S.35°E., 36 lks. dist.
- An Alder 6" dia., bears S.81°W., 26 lks. dist.

Survey by H.L. Eppstein - Wit: Frank Cain and W. Dailey - Jan. 25, 1929 (No source record found, see "old" corner book Vol. 1 Pg. 7)

Set corner from old witness tree in section 6, Maple.
Set 3/4" x 4" galv. Iron pipe. Mkd. new trees as follows:
4" Fir bears S.77°15'E., 65 lks.
10" Maple S.27°W., 17 lks.
20" Maple bears N.14°W., 23 lks.
No trees near in Section 31.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, crew - March 27, 1968 - C.S. File 53/66-63

Found - 3/4" I.Pipe and BTs as called for by Eppstein.
20" now 28" Maple, alive, N.14°W., 15.2 ft., shows good scar. Do not open.
10" now 16" Maple, alive, S.27°W., 11.2 ft., shows good scar. Do not open.
4" now 20" Fir, alive, S.77¼°E., 42.9 ft., faint scar. Rescribed "T21S R10W S6 CS BT"

Set brass cap at cor. mkd: County Surveyors Office

	R			R
T20S	11	S 36	S 31	10
T21S	W	S 1	S 6	W
		1968		

Deposit old corner pipe alongside brass cap.
New BT - 14" D.Fir, N.80°E., 83.60 ft. mkd. "T20S R10W S31 CS BT"

This corner lies on very steep S. slope about 300 ft. North of Smith River Road.

Fd. OK, Oct. 1989 by R. Stuntzner - M 109-13

(Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by Harvey Wilcox LS #2244- For: U.S. Forest Service -
Dec. 1990 - M 111-47 A-F

Found - 2½" brass cap on 1¼" I.P., 12" above ground with 1"
I.P. alongside.
30" Maple, SE trunk of tree with healed face, tags,
bears N.14°W., 15.2 ft. to side center.
21" D.Fir, healed face, tags, bears N.80°E., 83.6 ft
37" D.Fir, healed face, tags, bears S.77°15'E., 42.9
ft.
39" Maple, healed face, tags, bears S.27°W., 11.2
ft. This tree trunk has blown down, retagged
another trunk of same tree, it bears S.25°30'W.,
14.20 ft.

Set Reference monument:
Standard U.S.F.S. disk "RM T20S R10W S31 S88°09'W
52.91' 1990 RLS 2244", bears N.88°09'E., 52.91
ft.

Fd. OK, Feb. 1992 by R. Stuntzner - M 114-80