

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & Sec. 31, T20-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 1 Page(s) 86)

Set post for ¼ sec. corner, from which
An Alder 30" dia., bears N.80°E., 19 lks. dist.
An Alder 12" dia., bears S.89°W., 54 lks. dist.

Survey by Frank M. Pumphrey, LS #1677 - For: International Paper Co. - Aug. 1980 - M 85-37

Set 5/8" x 30" rebar with alum. cap mkd. "¼ Sec. 36 31".
Set 4" below surface, from which
3/4" Iron pipe bears N.82°11'30"E., 298.22 ft.
3/4" Iron pipe bears S.55°46'56"E., 287.06 ft.
Fence post with 16p nail in top of post bears N.56°E.,
33.3 ft.
Fence post with 16p nail in top of post bears S.33°E.,
36.2 ft.
Fence posts are tagged and corner lies in middle of field.

Fd. OK, Dec. 1990 - M 111-47 A-F